

Coast Wire & Plastic Tech., Inc.

A LATSHAW ENTERPRISE
1048 BURGROVE ST.
CARSON, CA 90746

(310) 639-9473 Phone

(310) 763-2225 Fax

METACLAS P/N: **81-79271270**

Revision: **None**
CWPT Part Number: **07-0536**
Revision: **None**
ECO Number **None**

Cable Specification

Cable, 37/C 20 AWG Shielded

CONDUCTOR 20 AWG

Wire Size & Type: 20 AWG (19/32) Tinned Copper, 10-0100-187
Nom. Wire Diameter: 0.040
Spark Test: 6000V
Insulation Type: SR-PVC 105C 600V
Nom. Ins Thickness: 0.009
Conductor Diameter: 0.058
Tolerance (+/-): .002"
Colors: See Color Chart

ASSEMBLY

Core Cabling: 1 + 6 + 12 + 18 Cabled
Nom. Diameter: 0.411
Nom. Lay Length: 4.87
Lay Direction: Left
Drain: 20 AWG (19/32) Tinned Copper, 10-0100-187
Shield: Aluminum/Polyester (100% Coverage, 25% Min. Overlap, Foil facing Inward), 20-0350-05



JACKET

Material Type: Gray Glossy PVC, 80C, 81A.
Nom. Jkt Thickness: 0.032
Cable Diameter: 0.475
Tolerance (+/-): .016"
Print: Ink Color Ink Jet Black
Legend: E64207 AWM STYLE 2464 80°C 300V 20/27C -- RoHS -- LL58231 CSA AWM I/II A/B 80°C 300V FT1

TESTS

Test 1: Continuity
Test 2: Shorts
Test 3: Physical/Dimensional

MISCELLANEOUS

Put Ups: 1,000 on 24" Reel
Reel: Wood 14 lbs.
Weight: 242 lbs/1,000 ft.
Total Weight: 256 Lbs.

APPROVALS

Singles: UL 1061 (80C, 300V)
Final Product: UL 2464 (80C, 300V)

Drawn By: Michael S. Howard

Title: Mgr. Engineering

Date: 10/08/2007

Checked By: _____

Title: _____

Date: _____

Approved By: _____

Title: _____

Date: _____